



Internal Dimensions	20' Standard	40' Standard	40' High Cube	20' Open Top	40' Open Top	20' Flat Rack	40' Flat Rack	20' Reefer	40' Reefer	40' Reefer High Cube
Length (mm)	5886 → 5940	12040 → 12062	12040 → 12069	5897 → 5905	11995 → 12020	5920 → 5952	12020 → 12092	5420 → 5450	11450 → 11550	11450 → 11550
Width (mm)	2340 → 2370	2340 → 2355	2348 → 2373	2330 → 2348	2285 → 2315	2310 → 2389	2380 → 2404	2250 → 2280	2250 → 2280	2250 → 2280
Height (mm)	2380 → 2410	2370 → 2377	2676 → 2709	2300 → 2345	2300 → 2360	2090 → 2175	1987 → 2002	2120 → 2260	2120 → 2200	2450 → 2550
Door opening										
Height	2275 → 2286	2270 → 2275	2577 → 2587	2240 → 2317	2220 → 2315			2020 → 2220	2020 → 2160	2340 → 2480
Width	2317 → 2335	2330 → 2355	2335 → 2340	2206 → 2325	2265 → 2315			2200 → 2280	2200 → 2280	2200 → 2280
Weights										
Max. Gross (kgs)	20320	30480	30480	20320	30480	20320	30480	24000	30400	30400
Tare (kgs)	2150	3600	3720	2300	3900	2970	5600	3200	4900	4900
Max. pay load	18170	26880	26760	18020	26580	17350	24880	20800	25500	25500
Cubage	32 → 34	67 → 68	75.5 → 77.5	31.6 → 32.7	65 → 67	30.5 → 32.5	56 → 58	28 → 29	57 → 58	66 → 67